
INDEX

# **Bronze Gate Valve**

### Class 200 • SIB • OS&Y • Rising Stem • Threaded Ends



#### Product no. 115100 - 200


Size Range: 1/2 through 2 inches Max. temperature limit is 450°F (232°C) • Threaded Ends

**Working Pressures** Non-Shock: 200 psi Steam, Basic Rating 400 psi Cold Working Pressure

#### Features

- · Rising Stem
- · Outside Screw and Yoke
- Solid Wedge Disc
- Full Ports
- · Back Seat
- Integral Bronze Seat
- MSS Specification SP-80
- · Easy to lubricate to ease operation and prevent wear.

For more details please contact: export@oswalvalve.com



### **Principal Parts & Materials**

Part	Material	ASTM
Body & Bonnet	Bronze	B62 alloy 83600
Disc	Bronze	B62 alloy C83600
Yoke sleeve	Brass	B16 alloy C36000
Stem	Brass	B16 alloy C36000

# Dimensions and Weights Millimeters - Kilograms

DN	1/2" 15	3/4'' 20	1" 25	1 1/4" 32	1 1/2" 40	2" 50
А	60	60	70	80	90	100
В	145	150	170	190	225	275
С	85	85	85	85	115	115
WTS.	1.20	1.40	1.70	3.00	3.50	4.50