


Bronze Gate Valve

Class 300 · Screwed in Bonnet • Rising Stem • Threaded Ends



Product no.112100 - 300

Size Range:

1/2 through 3 inches
Max. temperature limit is 450°F (232°C)


Working Pressures Non-Shock:

300 psi Steam, Basic Rating 1000 psi Cold Working Pressure 1/2" to 2" - (15mm - 50mm) 600 psi Cold Working Pressure 2.1/2" to 3" - (65mm-80mm)

Features

- · Rising Stem
- Screwed Bonnet
- Solid Wedge Disc
- Threaded Ends
- · Full Ports
- · Back Seat
- · Integral Bronze Seat
- · Recommended for WOG
- · MSS Specification SP-80

For more details please contact: export@oswalvalve.com



Principal Parts & Materials

Part	Material	ASTM
Body	Bronze	B62 alloy 83600
Bonnet	Bronze	B62 alloy 83600
Disc	Bronze	B62 alloy 83600
Stem	Brass	B16 alloy C36000

Dimensions and Weights

Millimeters - Kilograms

DN	1/2" 15	3/4" 20	1" 25	1 1/4" 32	1 1/2" 40	2" 50	2 1/2" 65	3" 80	4" 100
Α	60	60	70	80	90	100	-	-	-
В	130	160	190	215	250	305	-	-	-
С	55	65	70	85	95	105	-	-	-
WTS.	0.70	1.000	1.30	1.70	2.40	3.20	-	-	-