
# <u>o swalvalve</u>

## Bronze Gate Valve (Transformer)

### Class 2 • SIB • N-R Stem • S/F End • Indicator Type • Locking Rod



#### Product no. 111200ISFIL


#### Size Range:

1/2 through 4 inches

Max. temperature limit is 450°F (232°C)

## Working Pressures / Temperature Rating:

50 lbs/in<sup>2</sup> at 250 °F Transformer Oil 3.5 bar at 121 °C Transformer Oil 650 kPa at 121 °C Transformer Oil



#### Features

- Non Rising Stem
- Screwed Bonnet
- Flanged Ends are plain faces with two v-shaped concenttric grooves between the port and bolt holes.
- Full Ports
- PTFE Gland Packing
- · Integral Bronze Seat
- · Recommended for Transformer Oil
- · Powder Coated Alumnium Handwheel
- · Powder Coated Indicator with Locking Rod

For more details please contact: export@oswalvalve.com

Above size 4" also avaliable on request

TESTING HYDROSTATIC: BODY: 24 Kg/Cm<sup>2</sup>

SEAT : 16 Kg/Cm<sup>2</sup>

#### **Principal Parts & Materials**

Part	Material	IS
Body	Bronze	318 LTB2
Bonnet	Bronze	318 LTB2
Disc	Bronze	318 LTB2
Stem	Brass	319 GR2

#### **Dimensions and Weights**

Millimeters - Kilograms 1/2" 15 1" 2" 50 3/4" 20 DN 1 1/4" 1 1/2" 2 1/2" 3" 80 25 32 40 65 100 110 65 70 80 90 100 125 140 175 А В 120 135 140 165 190 215 260 285 350 С 60 65 75 75 95 110 125 125 175 0.90 1.30 3.50 4.50 9.00 18.00 WTS. 1.80 2.30 6.60