


## **Bronze Gate Valve (Transformer)**

## Class 150 • SIB • NRS • Flanged Ends • Indicator Type • Lock. Rod



### Product no. 111200AIL


#### Size Range:

1/2 through 4 inches

Max. temperature limit is 450°F (232°C)

# Working Pressures / Temperature Rating:

50 lbs/in² at 250 °F Transformer Oil 3.5 bar at 121 °C Transformer Oil 650 kPa at 121 °C Transformer Oil




#### **Features**

- · Non Rising Stem
- · Screwed Bonnet
- Flanged Ends are plain faces with two v-shaped concenttric grooves between the port and bolt holes.
- Full Ports
- PTFE Gland Packing
- · Integral Bronze Seat
- Recommended for Transformer Oil
- · Powder Coated Alumnium Handwheel
- · Powder Coated Indicator with Locking Rod

For more details please contact: export@oswalvalve.com

Above size 4" also avaliable on request

TESTING HYDROSTATIC: BODY: 24 Kg/Cm<sup>2</sup> SEAT : 16 Kg/Cm<sup>2</sup>



### **Principal Parts & Materials**

Part	Material	ANSI
Body	Bronze	B62 alloy 83600
Bonnet	Bronze	B62 alloy 83600
Disc	Bronze	B62 alloy 83600
Stem	Brass	B21 alloy C48200

### **Dimensions and Weights**

Millimeters - Kilograms

DN	1/2" 15	3/4" 20	1" 25	1 1/4" 32	1 1/2" 40	2" 50	2 1/2" 65	3" 80	4" 100
Α	80	90	100	110	120	135	165	185	230
В	120	135	140	165	190	215	260	285	350
С	60	65	75	75	95	110	125	125	175
WTS.	1.40	1.90	2.80	3.30	5.50	6.30	9.40	13.60	24.20