


Bronze Globe Valve (Transformer)

10K • Screwed in Bonnet • Rising Stem • One End Flanged



Product no. 122300JSF

Size Range:

1/2 through 2 inches

Max. temperature limit is 450°F (232°C)

Working Pressures / Temperature Rating:


50 lbs/in² at 250 °F Transformer Oil 3.5 bar at 121 °C Transformer Oil 650 kPa at 121 °C Transformer Oil

Features

- · Rising Stem
- · Screwed Bonnet
- Flanged Ends are plain faces with two v-shaped concenttric grooves between the port and bolt holes.
- PTFE Gland Packing and Seat Disc
- Integral Bronze Seat
- · Powder Coated Alumnium Handwheel
- Recommended for Transformer Oil
- Disc Holder Spun with stem up to size 2" and above retained by a threaded ring

For more details please contact: export@oswalvalve.com

Above size 4" also avaliable on request



TESTING HYDROSTATIC: BODY: 24 Kg/Cm² SEAT : 16 Kg/Cm²

Principal Parts & Materials

| Part | Material | JIS |
|--------|----------|--------------|
| Body | Bronze | BC6 |
| Bonnet | Bronze | BC6 |
| Disc | Bronze | BC6 |
| Stem | Brass | H3250 C 3601 |

Dimensions and Weights

Millimeters - Kilograms

| DN | 1/2" 15 | 3/4" 20 | 1" 25 | 1 1/4" 32 | 1 1/2" 40 | 2" 50 | 2 1/2" 65 | 3" 80 | 4" 100 |
|------|------------|------------|----------|--------------|--------------|----------|--------------|----------|-----------|
| Α | 70 | 80 | 90 | 100 | 115 | 135 | 165 | 185 | 215 |
| В | 90 | 110 | 120 | 140 | 155 | 170 | 210 | 225 | 280 |
| С | 60 | 65 | 75 | 75 | 95 | 110 | 125 | 125 | 175 |
| WTS. | 1.00 | 1.50 | 2.40 | 4.50 | 5.50 | 6.70 | 8.10 | 12.30 | 22.10 |